

Inspection Processes and Results



Stephen Berkshire – Chief Inspector MID

Tuesday, March 26th, 2019 12:00 Noon – 13:00 P.M.



MID History

"...and new Rule 124 added, to provide a system of checking by the A.R.A. Mechanical Inspection Department and authority for refund of proper charges detected by such checks, in the Interchange Rules instead of the Supplementary Regulations." Rule 124 was continued in place in 1934 when A.R.A. became the A.A.R.





MID - Benefits

- Safe and efficient interchange of equipment
- Increased utilization of fixed assets and rolling stock
- Industry self-regulation
- The support of a seasoned technical inspection/auditing team, with a 88 year tradition of serving the Rail Industry's needs







MID Inspections

D.	Scr	ap Inspection		Maj	Mod	Min	Rule Violation	
	Scr	ap Material Inspection	15		<u> </u>			Interchange Rules 83, 120
	a. (Component Materials		aspected				
			Condemn	Non-Condemn				
_	1	Air hoses						
	2	Adapters						
	3	Brake shoes						
	4	Truck bolsters						
	5	Brake beams						
	6	Coupler knuckles						1
	7	Coupler bodies						1
	8	Coupler yokes						
	9	Coupler component						
	10	Draft gears						
-		Truck side frames						
_		Truck springs						
		Other?						
	Ret	pair Practices						
		Brake			-			Interchange Rules 2 - 13
	a	Air Brake Test Informa	tion verified fo	r cars on repair				intereninge stores a st
		track?						
	b.	Single Car Air Brake T	ests performed					
		reported as required?						
	с.	Single Car Test device,	Brake cylinde	r pressure gage				
		and 28mm test coupling	g in-date?					
	d.	Brake Cylinder measur	ement tap appl	ied?				
	e.	Daily Test of SCABT of	levice properly	demonstrated?				
	f.	Single Car Air Brake T	est properly de	monstrated?				
		Hand Brake inspected a						
Т	h.	Proper piston travel and	d Decals/Sticke	rs as required?				
		Air hose clearance and						
		Model 3050, 3050-A, 3						
		cocks removed at time						
		Is set & release done in						
	1.	Are they checking & cl	eaning the refl					
		properly?						
	m.	Other?						
2.		ıpler/Draft Gear						Interchange Rules 16-22
		Draft systems inspected						
		Use of coupler gages a						
		Coupler and draft comp	oonents being r					
		condemnable defects?						
1		With coupler removed						
		unit yoke/endcap wear	gage?					
		Other?						
'	e.	Other:						

	GUIDE FOR CERTIFICATION AND INSPECTION OF WHEEL SHOPS									
Routin	e 🛛 Sp	ecial 🔲	Shop Certific	ration 🔲	Follow	up Inspect	ion 🔲			
M-100	Approved 🛛		ISO Approve	ed 🔲						
SR = S	ee Report At	tachments	Y/N	N/A	NI = N	ot Inspected	l			
#			D WHEELS			Maj	Mod	Min		
1	Equipment and Practices (Mounted Sets Checked for Bent Condition, 0.001 for each 1" separation from roller to that inductors (Minimum of 5.5" apart) Two dial indicators required if checked between centers. Checked for the second seco									
2	Sizes-Same Size, mounts Rule 1.4		for turns sets, the							
3		Mounted Wheel Set EARINGS NOT IN		WHEELSST	OPED					
4	HAS RUST PRV	ENTATIVE BEEN WHEEL SETS POS	APPLIED Rul	e 1.7.4						
5		TAL CONTACT D								
#			LATHES			Maj	Mod	Min		
6	should not excee	ces (Plane 0.045" & d 2/16" from one fla	nge to the other	Rule 1.5.4						
7		ractices (Within On ROW /WIDE FLAN								
8		(AAR 1-B Profile V "Limit, etc.) Rule		2" Gage, Exces	sive					
9	Tape Sizes (Tape	Sizes Verified With ence maximum. Ru	1 Tape Gage, O1	ie tape differenc	ce max,					
10	Are refinished tre	ads being UT per Ult	rasonic section o	f this form						
11	Total number of wheelsets:	Wheel Lathes:	Total numbe	er of newly mac	hined					
#		IC INSPECTION				Maj	Mod	Min		
12	Detect flaws Bet Reference Standa	ractices (5 MHz Tra ween ½" & 2", Suita rd simulating defec rel III, etc.) TYPE N	ble Couplant, A ts, Using DAC,	fter final machi. Written Approv	ining, ed					
13	Recalibration (Damage to system, 8 hours, etc.) Rule 2	change in transc							
14	Operators SNT-T TC-1A Qualified Rule 2.10.8.1	C-1A Certified (Eq , Level III available	uipment Set-Up , Proof of Certif	ication, etc.)						
15	Total number of Checked:	inspection equipmen	nt: Total	number of Wh	eel sets					
		-					MD03-CL-R	EV 01-16-19		

Association of American Railroads S-477 Manual of Standards and Recommended Practices	,	MD02
APPENDIX A A GUIDE FOR SHOP CERTIFICATION INSPECTORS FOR APPROVED CONTROL VALVES		
Name of Company: Company Name		
Location of Air Brake Shop: City, State		
Company Initials: Company Initials		
Shop Code Letters: Shop Code Letters		
Date of Inspection: Month, Day, & Year		
Type of Air Brake Valves Reconditioned: List type of valves		
Type of Inspection: List Type of Inspection Shop Approved [] M-1003 Certified [] Shop Dispproval [] Recommend Follow-up Inspection [] Commany Recenteditive(): Name & Title Name & Title		
		\dashv
Inspector: Inspectors Name & Title	v	_
The following items constitute general guidance for a shop inspector. The inspector must also ensure that control valve procedures are in compliance with the applicable shop maintenance manual.	Ē	N O
1. Copy of Maintenance Instruction, latest revision is available and work is being performed in accordance		
with instructions? 2391, Sup. 3 & 4 3/07; NYR-429 3/30/18 Rev. 11; NYR-332 7/23/18 Rev. 17 2. Copy of Test Instruction. latest revision is available at test rack and is being used? 5039-19. Sup. 1 9/94		
& 2 6/17; C Test Coden are used at all facilities except NYAB facilities. NVT-1199-C 830/18 Rev. 8; NVT-1200-C 8/28/14 Rev. 6; <u>T Test Codes are only used at NYAB facilities</u> . NVT-1199-S 7/16/2018 Rev. 25; NVT-1200-S 8/23/14 Rev. 19		
 Copy of Gauge Instruction, latest revision is available as required, condemning gauges are available at appropriate locations and work is being performed in accordance with instructions? 2391, Sup. 3 3/07; 2356- 3, Sup. 1 5/96 		
 All cleaning and re-lubrication of valve portions is done at a suitable bench in a clean well-lighted location? 2391 Sup. 3 & 4; NYR-332; NYR-429 		
 Valve portions and parts are being adequately cleaned? 2391, Sup. 3 & 4; NYR-332; NYR-429 		
 Removable chokes are being removed for cleaning, new felt filters are being applied, and threads are lubricated for reapplication. 2391 Sup. 3; NYR-332; NYR-429 		
7. Approved lubricants are being used? 2391 Sup. 3 & 4; NYR-332; NYR-429		
 Approved thread sealant is being used? 2391 Sup. 3 & 4; NYR-332; NYR-429 Modifications to control valves are being made in accordance with the maintenance instructions in 		
Paragraph 2.2 above? 2391, Sup. 3 & 4; NYR-332; NYR-429 10. Test racks are being properly tested in accordance with test specifications in Paragraph 2.3 above, and		
dates being tagged or stenciled on the rack? 5039-19, Sup. 1 & 2.		
 An occasional reteit and examination of valve portions is made to determine if portions have been properly tested and repaired. 5039-19, Sup. 1 & 2, Rule 7.3.5; NYT-1199-C; NYT-1200-C; NYT-1199-S; & NYT-1200-S. 		
 Is new rubber material being used? Are shelf life and storage requirements being met? Are rubber parts manufactured by an M-1003 certified facility? 2391, Sup. 3 & 4; NYR-429; NYR-332; FM 4.B.4 		
13. Shop air supply is clean, dry and adequate?		
14. Observe that special tools being used are not damaging parts? 2391 Sup. 3 & 4; NYR-429; NYR-332		
15. Approved shipping covers being used? 2391, Sup. 3 & 4; NYR-429; NYR-332		

































					ASSOCIAT	ION OF AME	RICA	N R/	AILR(DAD	S - E	ILLI	NG R	EPA	IR C/	ARD)						
REPAIRI	NG PA	RTY			REP AIRING PART	INVOICE NO.							DOCI	UMEN	IT RE	FER	ENCE	NO					
CAR INI	TIAL				CAR NUMBER				KIND	of	AR						LOA	D/EMI	YTY				
REPAIR	DATE				CAR NUMBER SPLC DETAIL SOURCE				REP/ DEFI	AIR I	CARD	PAR			-		DEFI	стс	ARD	DATE_		_	
Location			Job									orting	informa						Why	Jab			
on Car	QTY	cc	Code App	OFR	Description of Repairs Made	Component TagID	-		PLIED			f.m.	140		EMOVE:			fm		Code Revd		Resp Net Code Charg	
Car		-	~~~	н	repair error	Tag to		- 10				1.10		-		CL.				10110	-		Charge
		-	-	\vdash			-		⊢			-	-		-		-	-	-	<u> </u>	-	-	
				\vdash					-			-			-		-	-		-	-	-	
				\square					-									-		-	-	-	
		-	-	\square			-		⊢	-		-			-		<u> </u>	-	-	<u> </u>	-	-	
			-	\vdash					-			-			-		-	-		<u> </u>	-		
				н			-		-			-	-		-		-	-	-	<u> </u>	-	-	
																		_					
		-	-	-			-	-	-	-		-			-		-	-	-	<u> </u>	-		
		-	-	\vdash			-	-							-		-	-	-	—	-		
		-		н			-		-			-	-		-		-	-	-	<u> </u>	-	-	
							-			_								_			-		
		-	-	\vdash			-		-	-		-			-		-	-	-	—	-	\vdash	
		-								_					_			_	-		TOTA		

RULE 83 – PREPARATION OF ORIGINAL RECORD OF REPAIR AND BILLING REPAIR DATA

- All items of repairs must be covered in proper detail on the original record of the repairs and signed by party authorized to vouch for correctness of same.
- The following basic information must be shown on the original record of repairs.
 - a. Reporting marks (car initial)
 - b. Car number
 - c. Kind of car (not mandatory for Group Billable repairs).
 - d. Date repairs completed
 - e. Standard Point Location Code (SPLC)
 - f. Load/Empty indicator (not mandatory for Group Billable repairs)
- Detailed records must be kept for ready reference, either at point where repairs are made or Billing Repair Data is prepared. Retention period will be in accordance with current Regulations but in no case less than a minimum of 24 months from date of repair.



EHMS / UMLR / INTERNET

Need this access for ...

- Required information
- Updating information
- CID registration
- ➤ MD forms
- ≻QA forms



www.shutterstock.com · 10204498







GENERAL WELDING REQUIREMENTS






welding processes require personnel to prepare the material so it as free as possible from rust, scale, or oil. This provides a clean surface to perform a good sound weld



ompany na						
	source specification			Mex	Date	
	coedure qualitoat essies)	ion test record(s) re	0	Type		
				1994	Adventio, name	al, etc.)
inde of trans	dar for GMAN			Contractioning, Adviced, while	Transfer and	
_				College Brite Br		
DINTS	0.000			ATINGS		
ce cr west	es konstel			dinesa		_
1000				orete		
	Tites No			20er	Rehed Index To dat	
acking met	nai hore		_	-	and the second second	
occve weld						
		ioth sides				
ASE META						
	stication type and					
Support et						
Nickness ra						
Support M	ne .					
Thickness						
isse metal p	reparation					
LLER ME						
pecificator						
Sessification						
OSIDORS			P3	EHEAT		
ballion of g	0048		Pa	rheid temperature		
to rolled	let		Pa	rheat temperature	max	
rograssion						
AS	2			1000		
hielding ge		Now rate	- 16	ox rofe		
LUX						
			51.0 Z.S. N.			
			TECHNIQU			
Pass	Electrole	Electrical Cha	racteristica	Stand	Melting	Wire Feed
No.	504	Amperes	Volta	Speed	Rate	Speed
12						
	and the state	a fabrication seque	10.00		And the second second	and a second second
This proced D15.1.1		a Noncation sergue d Webbing Specifics			a research of vari	arrest System in 1
	(new)		the second second			
Authorized I					Date	





2018 – Top Exception	n Areas Noted
Material Storage	422 = 23.3 %
Outbound Inspection	415 = 22.9 %
Wheel Sets	189 = 10.4 %
Air Brake Test or Device	189 = 10.4 %
Publication Items	78 = 4.3 %

NOTE:Welding items66 exceptions = 3.6 %Billing and Gage (both had)61 exceptions = 3.4 %





- Inspectors document activity from working papers and forward reports to the office of the Chief Inspector MID within 7 days of the particular inspection activity
- Reports are reviewed within fifteen days of receipt from field
- The Chief Inspector MID and/or the Executive Director, Rules and Standards review and process field inspection reports
- Policy prohibits field inspectors from distributing report copies



Reporting Process

- Requests for copies of reports should be addressed to:
 - Chief MID Mechanical Inspection Transportation Technology Center, Inc. 55500 DOT Road Pueblo, Colorado 81001 or via email using the address - <u>mid@aar.com</u>
- Policy prohibits field inspectors from distributing report copies



- OTL inspection goal for 2018 was 100 inspections.
- Unfortunately we did not achieve our goal, completing 96 inspections, falling short by 4 inspections.




Open Top Loading










Data reflects: January 1, 2019 AAR Registry of M-1003 Certified Facilities




Total AAR Accredited Auditors: 54

Total Audits: 780

Average # of Findings Per Audit: 1-2









Noncompliance - 30 day written response Transgression - 30 day written response Item of concern - no written response










Activities for 2018		Planned
Freight Car Shop Inspections (Routine)		600
TOFC Inspections		56
Air Brake Shop Inspections		30
Wheel Shop Inspections - Non-Member		8
Wheel Shop Inspections - Railroad		10
Wheel Shop Inspections - Private		62
Wheel Shop Inspections - Transit		16
Roller Bearing Shop Inspections - Non-Member		4
Roller Bearing Shop Inspections - Railroad		2
Roller Bearing Shop Inspections - Private		24
Axle Plating Shop Inspection - Private		12
Roller Bearing Mounting Inspections		4
Status 9A (End Cap Removal/Reapp) Inspections		2
Misc. Certification Inspections - As Requested		10
M-214 Inspections		40
M-970 Inspections		14
Rule 88 Inspections - As Requested		14
Special Inspections - As Requested		8
Follow-Up Inspections - As Requested		28
Test Observation Inspections (per day) -As Requested		80
Open Top Loading Inspections		100
Routine Inspection of Freight Car Builders		14
Quality Assurance Audits		318
Joint M-1003 (QA) Audits with BOE		120
	SUBTOTAL	1576
Technical Committee Support - Days		30
Training Received & Provided - Days		40
MID Management Support - Days		25
	TOTALS	1671



MID 2019 Activity Goals





How Do We Improve?




Self Audits

Better Training / Mentorship

Ask Questions of the Worker





Thank you!

Transportation Technology Center, Inc. 55500 DOT Road Pueblo, Colorado 81001 www.aar.com

